



## HDT1/12C Module

- Removable modules for the protection of data and communication lines against longitudinal and transverse surge effects.

| Type   |       | HDT1/12C Module      |
|--|-------|----------------------|
| Rated operating DC voltage   | $U_N$ | 0 ÷ 12 V             |
| Maximum continuous operating voltage DC  | $U_C$ | 14.4 V               |
| Spare module for   |       | 56 019, 56 019/NV    |
| <b>Designed according to standards</b>   |       |                      |
| Requirements and test methods for SPDs connected to telecommunications and signalling networks |       | IEC 61643-21:2000    |
| Safety of Flammability of Plastic Materials  |       | UL 94                |
| <b>Application standards</b>   |       |                      |
| Protection against lightning   |       | IEC 62305:2010       |
| <b>Ordering, packaging and additional data</b>   |       |                      |
| Mass   | m     | 18 g                 |
| Mass (including the packaging)   | m     | 29 g                 |
| Packaging dimensions (H x W x D)   |       | 26 x 98 x 73 mm      |
| Packaging value  | V     | 0.19 dm <sup>3</sup> |
| Customs tariff no.   |       | 85363010             |
| EAN code   |       | 8590681167892        |
| <b>Art. number</b>   |       | <b>56 019/M</b>      |



The link in the QR code leads to the online presentation of the **HDT1/12C Module**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit [www.hakel.com](http://www.hakel.com)



8590681167892