



## HDT1/24B Module

- Výmenné moduly pre ochranu dátových a oznamovacích vedení pred účinkami pozdĺžneho a priečneho prepätia.

Type		HDT1/24B Module
Menovité prevádzkové napätie DC	$U_N$	0 ÷ 24 V
Najvyššie trvalé prevádzkové napätie DC	$U_C$	28,8 V
Výmenný modul pre		56 004, 56 004/NV
<b>Navrhnuté podľa noriem</b>		
Ochrany pred prepätím zapojené do telekomunikačných a signálnych sietí. Požiadavky na spôsobilosť a skúšobné metódy		STN EN 61643-21:2002
Bezpečnosť horľavosti plastových materiálov		UL 94
<b>Inštaluje sa podľa noriem</b>		
Ochrana pred bleskom		IEC 62305:2010
<b>Objednávacie, obalové a doplnkové dáta</b>		
Hmotnosť	m	18 g
Hmotnosť (vrátane obalu)	m	29 g
Rozmery balenia (V x Š x H)		26 x 98 x 73 mm
Objem balenia	V	0,19 dm <sup>3</sup>
Colná nomenklatúra		85363010
EAN kód		8590681167946
<b>Katalógové číslo</b>		<b>56 004/M</b>



The link in the QR code leads to the online presentation of the **HDT1/24B Module**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit [www.hakil.com](http://www.hakil.com)



8590681167946