



B25M/M Vseries

- Removable modules for lightning impulse current and surge arresters type T1+T2.
- The products consist of gas discharge tube with high discharge ability.
- Installed at the boundaries of LPZ 0 – LPZ 2, in TN-S, TT power supply systems and in a special design also in IT power supply system.
- Balance the potential between the N and PE conductors in 1+1, 3+1 connection modes.
- Ensures zero leakage current through the PE conductor.

Type		B25M/M Vseries
Test class according to EN 61643-11:2012 (IEC 61643-11:2011)		T1, T2
Maximum continuous operating voltage AC	U_C	255 V
Impulse discharge current for class I test (10/350) N/PE	I_{imp}	25 kA
Nominal discharge current for class II test (8/20) N/PE	I_n	30 kA
Voltage protection level at I_{imp}	U_p	< 1.3 kV
Spare module for		16 040
Designed according to standards		
Requirements and test methods for SPDs connected to low-voltage power systems		IEC 61643-11:2011
Safety of Flammability of Plastic Materials		UL 94
Application standards		
Protection against lightning		IEC 62305:2010
Selection and erection of electrical equipment – Switchgear and controlgear		HD 60364-5-53:2022
Selection and application principles for SPDs connected to low-voltage power systems		CLC/TS 61643-12:2009
Ordering, packaging and additional data		
Mass	m	45 g
Mass (including the packaging)	m	56 g
Packaging dimensions (H x W x D)		26 x 98 x 73 mm
Packaging value	V	0.19 dm ³
Customs tariff no.		85363010
EAN code		8590681160411
Art. number		16 041



The link in the QR code leads to the online presentation of the **B25M/M Vseries**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakel.com



Internal diagram

