



PIVM PV 600/M Vseries

- Removable modules for lightning impulse current and surge arresters type T1+T2 intended for photovoltaic systems (PV).
- Contain a varistor with high discharge ability.
- Modules are equipped with internal disconnectors, which are activated when the varistors fail (overheat) and they are able to interrupt the DC current.
- Special construction of the internal disconnector allows installation without a back-up fuse.
- Ensure the equipotential bonding of plus and minus busbars of PV systems and the elimination of transient overvoltage resulting from the atmospheric discharges (including direct lightning strike to the PV system) or switching processes.

Type		PIVM PV 600/M Vseries
Test class according to EN 61643-11:2012 and EN 61643-31:2019		T1, T2
Maximum continuous operating voltage	U_{CPV}	600 V DC
Maximum continuous operating voltage (+/-)	U_{CPV}	600 V DC
Short-circuit current rating	I_{SCP}	10 kA
Impulse discharge current for class I test (10/350)	I_{imp}	6.5 kA
Nominal discharge current for class II test (8/20)	I_n	20 kA
Voltage protection level at I_n	U_p	< 2.6 kV
Spare module for		16 070, 16 071
Designed according to standards		
Requirements and test methods for SPDs for photovoltaic installations		IEC 61643-31:2018
Safety of Flammability of Plastic Materials		UL 94
Application standards		
Protection against lightning		IEC 62305:2010
Selection and application principles for SPDs connected to photovoltaic installations		CLC/TS 50539-12:2010
Low-voltage electrical installations – Photovoltaic (PV) systems		HD 60364-7-712:2016
Ordering, packaging and additional data		
Mass	m	70 g
Mass (including the packaging)	m	81 g
Packaging dimensions (H x W x D)		26 x 98 x 73 mm
Packaging value	V	0.19 dm ³
Customs tariff no.		85363010
EAN code		8590681119686
Art. number		16 072



The link in the QR code leads to the online presentation of the **PIVM PV 600/M Vseries**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakil.com



8590681119686

Internal diagram

