



HDT2/6C

- Designed for the protection of data and communication lines against longitudinal and transverse surge effects.
- Pluggable version.
- No interruption of communication bus when the module is removed.
- One pair or two pairs lines.
- Contains both 1st and 2nd stage of protection.
- The HDT*/*C range, in addition, contains a gas discharge tube between the PE and SH (shield) terminals for their galvanic isolation.
- Suitable for use in industrial applications, especially in low-voltage ESS, FDAS systems and also in measurement and control systems.

Type	HDT2/6C	
Testing category according to IEC 61643-21:2000 and EN 61643-21:2001	C1, C2, C3, D1	
Number of pairs	2	
Connector type	Screw terminals	
Rated operating DC voltage	U_N	0 ÷ 6 V
Maximum continuous operating voltage DC	U_C	7.2 V
Rated load current	I_L	0.5 A
C1 Voltage protection level at I_n (line/PE)	U_p	< 180 V
C1 Voltage protection level at I_n (line/line)	U_p	< 30 V
C1 Nominal discharge current (8/20)	I_n	1 kA
C2 Voltage protection level at I_n (line/PE)	U_p	< 350 V
C2 Voltage protection level at I_n (line/line)	U_p	< 40 V
C2 Nominal discharge current (8/20)	I_n	15 kA
C3 Voltage protection level at 1 kV/ μ s (line/PE)	U_p	< 15 V
C3 Voltage protection level at 1 kV/ μ s (line/line)	U_p	< 10 V
D1 Impulse discharge current (10/350) line/PE	I_{imp}	2.5 kA
D1 Total impulse discharge current (10/350)	I_{Total}	5 kA
Response time	t_A	< 30 ns
Data rate	1 Mbit/s	
Bandwidth	B	0 ÷ 1 MHz
Series impedance per line	1.8 Ω	
Parasitic capacitance	C	< 1.5 nF
Lightning protection zone	LPZ 1-2, LPZ 2-3	
Housing material	Polyamid PA6, UL94 V-0	
Degree of protection	IP20	
Operating temperature	θ	-40 ÷ 55 °C
Clamp fastening range (solid conductor)	0.2 ÷ 1.5 mm ²	
Tightening moment	0,5 Nm	
Installation	On DIN rail 35 mm	
Modular width	1 TE	
Operating position	Any	

Type		HDT2/6C
Remote signalling		No
Modular design		Yes
Article number of spare module		56 022/M
Lifetime		> 100 000 h
Designed according to standards		
Requirements and test methods for SPDs connected to telecommunications and signalling networks		IEC 61643-21:2000
Safety of Flammability of Plastic Materials		UL 94
Application standards		
Protection against lightning		IEC 62305:2010
Ordering, packaging and additional data		
Mass	m	79 g
Mass (including the packaging)	m	90 g
Packaging dimensions (H x W x D)		26 x 98 x 73 mm
Packaging value	V	0.19 dm ³
ETIM group		EG000021
ETIM class		EC000943
Customs tariff no.		85363010
EAN code		8590681167540
Art. number		56 022



The link in the QR code leads to the online presentation of the **HDT2/6C**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit www.hakel.com



Internal diagram

