



## MED ECO-line 4 kVA

- Transformers with reduced operational losses, composite core and vertical mounting are intended for the supply of equipment in medical locations.
- Thanks to the higher efficiency of operation, transformers help to significantly save electrical energy and thereby reduce the economic and environmental impact of operations.
- Produced with a voltage transfer of 230 / 230 V or 400 / 230 V, frequency 50 / 60 Hz, protection IP00, terminals IP20, insulation class F (155 °C) and maximum ambient temperature of 55 °C.
- Transformers have reinforced insulation and protective shielding between the primary and secondary winding.
- Equipped with two temperature sensors PT100, which allow them to work better with HAKEL ISOLGUARD insulation monitoring devices and provide the best possible basis for measuring the insulation condition and transformer heating.
- Transformers can be supplied in a steel case with IP23 protection.

Type		MED ECO-line 4 kVA
Primary supply voltage AC		230 V
Secondary voltage AC		230 V
Power	P	4 000 W
Transformer construction		Less operating losses
Frequency	f	50 ÷ 60 Hz
In-built temperature sensor		2 x PT100
In a steel cover		No
Protection class according to IEC 61140		I
Insulation class		F
Operating temperature	θ	-25 ÷ 55 °C
Degree of protection		IP00
Short-circuit resistance of the secondary side		Non resistant
Trigger current		Max. 8 times the rated current
Clamp fastening range (solid conductor)		2.5 ÷ 16 mm <sup>2</sup>
Clamp fastening range (stranded conductor)		2.5 ÷ 16 mm <sup>2</sup>
Recommended cross-section of connecting wires	S	4 mm <sup>2</sup>
Width		244 mm
Height		403 mm
Depth		176 mm
Short-circuit voltage	U <sub>k</sub>	2.1 %
No-load losses	ΔP <sub>0</sub>	16 W
Total losses	ΔP	110 W
Efficiency	η	97.3 %
Noise level		< 35 dBA
Recommended fuse protection		32 A/gG

## Designed according to standards

Particular requirements and tests for isolating transformers for the supply of medical locations		IEC 61558-2-15:2011
Safety of power transformers, power supplies, reactors and similar		IEC 61558-1:2005

## Application standards

Low-voltage electrical installations – Medical locations		HD 60364-7-710:2012
Electric installations in rooms for medical use		ČSN 33 2140, TNI 33 2140

## Ordering, packaging and additional data

Mass	m	45 kg
Customs tariff no.		85043200
EAN code		8590681174272
<b>Art. number</b>		<b>72 233/00</b>



The link in the QR code leads to the online presentation of the **MED ECO-line 4 kVA**. There, in addition to the always up-to-date data sheet, you will also find all diagrams and drawings, declarations of conformity, or 2D or 3D models and other necessary materials. For more information, visit [www.hakil.com](http://www.hakil.com)



## Internal diagram

